A Computational Study of the Influence of Boattail Plates on the Trailer Flowfield

Dan Flowers, Jerry Owens, Rose McCallen, Tim Dunn

Lawrence Livermore National Laboratory Livermore, CA

November 14, 1999



Several approaches are being used to simulate the GTS



SNL

Reynolds Average Navier-Stokes (RANS)/ Detached Eddy Simulation (DES)
Compressible Finite Volume Code
Average "Steady" Solution/Unsteady Solution
Widely used - may not predict drag correctly

LLNL


Large Eddy Simulation (LES)
Compressible Finite Element Code
Unsteady Solution of large scales/approximation of the small scales
Computationally intensive

Caltech

Direct Numerical Simulation/ LES
Vortex Method
Gridless
In development

Turbulent flow contains eddies ranging from largescale to small-scale






Large-eddy simulation captures the large-scale motion and approximates the small-scale motion.

all turbulent motions = large-scale motions + small-scale motions = 'resolved' scale + 'subgrid' scale $u_{\alpha} = \bar{u}_{\alpha} + u'_{\alpha}$




Streamwise Velocity

LES: instantaneous and/or time-averaged with 1 empirical parameter



RANS: only time-averaged with many empirical parameters



We are focusing on two areas




Simulating full GTS geometry

NASA 7'x10' wind tunnel tests

Course mesh ~ 6 million elements

Results will be validated with experiments



Effect of boattail plates on aerodynamic drag reduction

Modeling only back end to conserve elements Geometry based on GTS model Investigating fundamental flow phenomenon

Boattail plates have been shown to reduce drag



Full-scale truck in wind tunnel



Model in wind tunnel




Plates developed by Continuum Dynamics, Inc.

A recirculation zone forms in the boattail plate offset




This recirculation zone draws the wake in behind the body



Solving the 3D turbulent flow field requires extensive computational resources




Compressible flow simulation



Half of 3 million element grid

148 computational domains

148 processors on ASCI Blue massively parallel machine (IBM)




Domain decomposition

The problem size is approximately 3 million elements with 1 mm wall resolution



Grid on rear of trailer


Refinement at walls and plates



Resolution of the wall determines the time step

Computations predict the reduced wake size as seen in experiments






Effect of boattail plate length is being studied



Streamwise Velocity Component



Out of plane vorticity in trailer wake





Top View


Without plates

2" plates

2.5" plates







Summary



Boattail plates have been shown experimentally to reduce drag

FEM/LES is being used to understand the flow phenomena and the effect of plate length

Preliminary results indicate similar trends as the experiments

Validation of simulations with experiments is ongoing